

# Majestic Bianco Pulido Polished

CÓDIGO CODE	FORMATO FORMAT	CARAS ALEATORIAS RANDOM FACES
AT3112011PR	120x120	N/A
AT3126011PR	60x120	N/A



Resist. Deslizamiento  
Slip Resistance



UNE-ENV  
12633



## Tabla Técnica | Technical Chart | Scheda Tecnica

Porcelánico Esmaltado | Glazed Porcelain | Porcellanato Smaltato

**Bla**

EN 14411

 ISO 10545-2 ± 0.1% / ± 2% Diferencia Tamaño Size difference	 ISO 10545-2 ± 0.1% Rectitud Lados Straightness of side	 ISO 10545-2 ± 0.2% Horizont. Superficie Surface Flatness	 ISO 10545-3 0.07% Absorción de Agua Water Absorption	 ISO 10545-6 1500 Rev. Resistencia Abrasión Abrasion Resistance	 ISO 10545-9 Sin rotura - No crack Resist. Choque Térmico Thermalshock Resist.	 ISO 10545-12 Cumple - Pass Resistencia hielo Frost resistance	 ISO 10545-14 Clase 4 Resistencia Manchas Stain Resistance	 UNE 67-101 Mohs 4 Resistencia Rayado Scratch Resistance
--	---	---	---	---	--	--	--	--

## Embalaje | Packing | Imballi

Formato Size	Cajas Boxes			Pallet			Espesor Thickness	
	PZ/CJ Pcs/Box	m <sup>2</sup> /CJ m <sup>2</sup> /Box	KG/CJ KG/Box	CJ/Pl Box/Pallet	m <sup>2</sup> /Pl m <sup>2</sup> /Pallet	KG/Pl KG/Pallet	mm	inch
120x120	1	1,44	30	27	38,88	810	9	3 <sup>35</sup> / <sub>64</sub>
60x120	2	1,44	30	30	43,20	900	9	3 <sup>35</sup> / <sub>64</sub>

## Características Técnicas | Technical Characteristic | Caratteristica Tecnica

 Porcelánico Porcelain	 Rectificado Rectified	 Junta Mínima Min Join	 Pavimento Floor	 Revestimiento Wall
 Residencial Home	 Baño Bathroom	 Pulido Polished	 Tránsito Traffic	 Destonificado Shade Variation